

York Toilet Suite - T6009P

(P-Trap)



Ceramic Close Coupled Toilet Suite Fast Flow Rimless, Nanoglaze protection

Features:

- Economical and easy-to-install toilet suite
- Fast Flow Rimless design for easy-to-clean and hygienic toilet
- Gloss white finish with Nanoglaze surface protection provides anti-bacterial and grime-resistant qualities
- Large round easy-to-use flush button
- Thermoplastic (PP) quick release seat cover with stainless steel hinges

Details:

Cistern Bottom right inlet point

(Universal inlet - compatible with back entry or


bottom left inlet point - extra cost)

Pan Fast Flow Rimless design with Nano glaze protection


Traps P-trap installation

Seat PP quick release soft closing seat
Wels 4 Star rated, 4.5L/3L (3.5L average flush)

Setout 180mm (P-Trap)



FRONT VIEW | 90| 365 | 810 | 740 | 395 | 255 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 | 395 |



Additional Information

- Installation should be in accordance with AS/ NZS3500 standards.
- In order to fully benefit from warranty claims, please ensure products are installed by a licensed plumber.
- All measurements are in millimeters.
- -Dimensions are nominal and subject to normal ceramic manufacturing variations. Please allow
- +/- 15 mm tolerance.
- For mark-ups & roughing-in, always use actual product measurement.
- Specifications may vary without notice as part of our continuous improvement practices.

Maintenance & Care

- Toilet seat cover can be removed for cleaning by pressing quick release buttons and lifting up.
- Clean with a toilet brush or soft cloth/sponge using warm water and mild soap or detergent.
- Do not use any abrasive cleaners, liquids or pastes.
- Do not use solvents or corrosive liquids.
- Please do not close the seat cover forcibly to extend the soft-close function lifespan.

Check out our full range of products on our website:



BESTBM.COM.AU