

# Denver Toilet Suite - T6002R



# Ceramic Back To Wall Toilet Suite Fast Flow Rimless, Nanoglaze protection

#### Features:

- Sleek modern design sits flushed against the wall
- Fast Flow Rimless design for easy-to-clean and hygienic toilet
- Gloss white finish with Nanoglaze surface protection provides anti-bacterial and grime-resistant qualities
- Large round easy-to-use flush button
- Aminoplast (UF) quick release soft closing seat cover with stainless steel hinges

#### **Available Seat Covers:**

FSC243 Flat Seat - Default (20 mm lid profile)
TSC329 Thick Seat (30 mm lid profile)
SSC832 Slim Seat (20 mm lid profile)

#### **Details:**

Setout

Cistern Universal inlet - compatible with back entry or


bottom left/right inlet point


Pan Rimless - Tornado design with Nano glaze protection
Traps Universal - compatible with S or P-trap installation
Seat UF quick release soft closing seat


WELS 4 Star rated, 4.5L/3L (3.5L average flush)

70 - 170mm

Extendable to 220 mm (pipe: AD17, extra cost)







# **Additional Information**

- Installation should be in accordance with AS/ NZS3500 standards.
- In order to fully benefit from warranty claims, please ensure products are installed by a licensed plumber.
- All measurements are in millimeters.
- -Dimensions are nominal and subject to normal ceramic manufacturing variations. Please allow
- +/- 15 mm tolerance.
- For mark-ups & roughing-in, always use actual product measurement.
- Specifications may vary without notice as part of our continuous improvement practices.

# Maintenance & Care

- Toilet seat cover can be removed for cleaning by pressing quick release buttons and lifting up.
- Clean with a toilet brush or soft cloth/sponge using warm water and mild soap or detergent.
- Do not use any abrasive cleaners, liquids or pastes.
- Do not use solvents or corrosive liquids.
- Please do not close the seat cover forcibly to extend the soft-close function lifespan.

# **Installation Manual Video**



BESTBM.COM.AU

