

Venice Toilet Suite - T6088



Ceramic Back To Wall Toilet Suite Tornado Flush, Nanoglaze protection

Features:

- · Sleek modern design sits flushed against the wall
- Tornado Flush feature for a more efficient, thorough and quiet flush
- Gloss white finish with Nanoglaze surface protection provides anti-bacterial and grime-resistant qualities
- Large rectangular easy-to-use flush button
- Aminoplast (UF) quick release soft closing seat cover with stainless steel hinges

Available Seat Covers:

FSC243 Flat Seat - Default (20 mm lid profile)
TSC329 Thick Seat (30 mm lid profile)
SSC832 Slim Seat (20 mm lid profile)

Details:

Cistern Universal inlet - compatible with back entry or

bottom left/right inlet point

Pan Tornado Flush with Nanoglaze protection

Traps Universal - compatible with S or P-trap installation


Seat UF quick release soft closing seat
Wels 4 Star rated, 4.5L/3L (3.5L average flush)

Setout 70 - 170mm


Extendable to 220 mm (pipe: AD17, extra cost)

SIDE VIEW -145 400 -180 -70 - 220 -535

FRONT VIEW



TOP VIEW



Additional Information

- Installation should be in accordance with AS/ NZS3500 standards.
- In order to fully benefit from warranty claims, please ensure products are installed by a licensed plumber.
- All measurements are in millimeters.
- -Dimensions are nominal and subject to normal ceramic manufacturing variations. Please allow
- +/- 15 mm tolerance.
- For mark-ups & roughing-in, always use actual product measurement.
- Specifications may vary without notice as part of our continuous improvement practices.

Maintenance & Care

- Toilet seat cover can be removed for cleaning by pressing quick release buttons and lifting up.
- Clean with a toilet brush or soft cloth/sponge using warm water and mild soap or detergent.
- Do not use any abrasive cleaners, liquids or pastes.
- Do not use solvents or corrosive liquids.
- Please do not close the seat cover forcibly to extend the soft-close function lifespan.

Installation Manual Video



BESTBM.COM.AU

